

Sustainable Building Materials

Sustainable Building Materials – Quick Reference Notes

1. Why Sustainable Materials Matter

Goal	Typical Impact	How Sustainable Materials Help
Reduce carbon footprint	30–40% of global CO ₂ emissions come from construction	Lower embodied energy, carbon sequestration, renewable sourcing
Conserve natural resources	Massive extraction of sand, timber, minerals	Use recycled, rapidly renewable, or locally sourced feedstocks
Improve indoor environmental quality	Off-gassing, moisture problems	Low-VOC, breathable, moisture-regulating products
Enhance durability & life-cycle performance	Frequent repairs/replacements generate waste	Materials designed for longevity, easy maintenance, and adaptability

2. Classification of Sustainable Materials

Category	Representative Materials	Key Sustainable Attributes	Typical Applications
Renewable & Bio-Based	Bamboo, timber from certified forests, straw bale, hempcrete, cork, mycelium composites	Rapid growth, carbon sequestration, low embodied energy	Structural frames, wall infill, insulation, flooring
Recycled & Upcycled	Recycled steel, reclaimed wood, crushed glass, recycled concrete aggregate, plastic lumber, fly ash geopolymer concrete	Diverts waste from landfill, reduces virgin material demand	Structural members, decking, paving, concrete mixes
Low-Impact Minerals	Engineered gypsum, lime-based plasters, silica-based aerogels, basalt fiber	Low processing temperature, recyclable, high thermal performance	Interior finishes, fire-resistant panels, insulation

Sustainable Building Materials

Category	Representative Materials	Key Sustainable Attributes	Typical Applications
High-Performance Insulation	Cellulose (recycled paper), sheep wool, cork, wood fiber, vacuum-insulated panels (VIP)	High R-value per thickness, renewable, low VOC	Wall/roof/ceilings, retrofit upgrades
Green Concrete Alternatives	Geopolymer concrete, alkali-activated slag, carbon-cured concrete, ultra-high-performance concrete (UHPC) with supplementary cementitious materials (SCMs)	Up to 70% lower CO ₂ than Portland cement, can incorporate industrial by-products	Foundations, slabs, precast elements
Smart & Adaptive Materials	Phase-change materials (PCMs), thermochromic glazing, photocatalytic concrete	Energy-saving, improve indoor comfort, self-cleaning	Façades, interior walls, roofing

3. Material-Specific Deep Dives

3.1 Bamboo

- **Growth rate:** 3–5m/yr¹; harvestable in 3–5 years.
- **Strength:** Tensile strength 140–230MPa (comparable to mild steel).
- **Environmental credits:** Low embodied energy (~3–5MJ/kg¹); carbon sequestration up to 0.5tCO₂/m³.
- **Design considerations:** Needs treatment against insects & moisture; prefers engineered panels (laminated bamboo) for dimensional stability.

3.2 Hempcrete

- **Composition:** Hemp shiv + lime binder (often with pozzolans).
- **Thermal performance:** $\lambda \approx 0.07\text{--}0.12\text{ W/m}\cdot\text{K}$ ¹; R-value ≈ 2.5 per 100mm.
- **Carbon impact:** Net negative (CO₂ absorbed during hemp growth exceeds emissions from lime curing).
- **Limitations:** Not load-bearing; used as infill with timber or steel frame.

Sustainable Building Materials

3.3 Recycled Steel

- Embodied energy: ~20% of