

Introduction to Optical Communication

Introduction to Optical Communication Systems

(Key concepts, components, and fundamentals for a first-time learner)

1. What Is Optical Communication?

Aspect	Description
Definition	Transmission of information using light (usually in the infrared or visible spectrum) as the carrier.
Why Light?	• Very high carrier frequency ? huge bandwidth • Low attenuation in glass/fiber • Immunity to electromagnetic interference
Typical Media	• Optical fiber (single-mode, multimode) • Free-space (air, vacuum, water) • Integrated photonic waveguides

2. Core Components of an Optical Link

1. Transmitter

- **Light Source** – Laser diode (LD) or Light-Emitting Diode (LED).
- **Modulator** – Directly modulated (current drives intensity) or external modulator (Mach-Zehnder, electro-absorption).
- **Driver Electronics** – Generates the electrical data signal and bias for the source.

2. Optical Fiber (Transmission Medium)

- **Core** – Central region where light propagates.
- **Cladding** – Lower-index layer that confines light by total internal reflection.
- **Coating/Buffer** – Mechanical protection.

3. Receiver

- **Photodetector** – PIN or avalanche photodiode (APD) converts light to current.
- **Transimpedance Amplifier (TIA)** – Turns photocurrent into voltage.

Introduction to Optical Communication Systems

- **Signal Processing** – Clock recovery, equalization, decoding.

4. Auxiliary Elements

- **Couplers / Splitters** – Combine or divide signals.
- **Amplifiers** – Erbium-doped fiber amplifiers (EDFAs) for long-haul links.
- **Wavelength Division Multiplexers (WDM)** – Multiple wavelengths share a single fiber.

3. Types of Optical Fibers

Type	Core Diameter	Typical Use	Key Characteristics
Single-Mode Fiber (SMF)	~8–10 μm	Long-haul, high-speed backbone	Supports one propagation mode ? low modal dispersion, >10 Gb/s over 100 km
Multimode Fiber (MMF)	50 μm or 62.5 μm	Data centers, LANs (2 km)	Multiple modes ? higher modal dispersion, limited bandwidth-distance
Graded-Index MMF	50 μm	Improves MMF performance	Refractive index gradually decreases ? reduces modal dispersion

4. Basic Link Budget

A link budget predicts the received optical power (P_R) and verifies that it exceeds the receiver sensitivity.

$$[P_R(\text{dBm}) = P_T(\text{dBm}) - \underbrace{L_{\text{fiber}}}_{\text{attenuation}} - \underbrace{L_{\text{splice}}}_{\text{connections}} - \underbrace{L_{\text{connector}}}_{\text{each}} + G_{\text{amp}}]$$

- P_T – Transmitter output power (dBm).
- L_{fiber} – $(\alpha \times L)$ where (α) is attenuation (dB/km) and (L) is length