

Introduction to Land Survey Problem Solving

Introduction to Land Survey Problem Solving

Designed as a quick-reference guide for students and practitioners

1. What Is Land Surveying?

Aspect	Description
Purpose	Determine the precise positions, elevations, and dimensions of points on the Earth's surface.
Key	• Boundary lines
Outputs	• Topographic maps • Construction staking • Geographic Information System (GIS) data
Typical Users	Land planners, civil engineers, architects, real-estate professionals, government agencies, utility companies.

2. Core Concepts & Terminology

Term	Meaning
Control Point	A surveyed point with known coordinates and elevation that serves as a reference for other measurements.
Datum	The reference surface (horizontal & vertical) used to define coordinates (e.g., NAD83, WGS84).
Coordinate System	Framework for locating points (e.g., State Plane, UTM, local grid).
Traverse	A linked series of measured lines and angles used to establish a network of points.
Intersection	Determining a point by measuring angles from two known points.
Offset	A perpendicular distance from a known line to a point of interest.
Stakeout	Placing physical markers on the ground to represent design coordinates.
Precision vs. Accuracy	<i>Precision</i> = repeatability of measurements; <i>Accuracy</i> = closeness to true value.

Introduction to Land Survey Problem Solving

3. Typical Survey Problems & How to Approach Them

Problem Type	Typical Goal	Standard Solution Steps
Boundary Determination	Locate property lines and corners.	1. Gather legal documents (deeds, plats). 2. Locate existing control points. 3. Perform a closed traverse or resection to tie to control. 4. Compute bearings & distances; adjust for errors (Bowditch/least squares).
Topographic Mapping	Produce contour maps of terrain.	1. Establish a grid of control points. 2. Conduct elevation surveys (leveling, GPS RTK, total station). 3. Interpolate elevations; generate contour lines (usually 0.5m to 5m intervals).
Construction Staking	Translate design plans to ground positions.	1. Import design coordinates (CAD/DXF). 2. Transform to field coordinate system using control points. 3. Use total station or GNSS rover to stake each point.
Utility Location	Identify underground/overhead assets.	1. Obtain existing utility maps. 2. Perform subsurface probing or electromagnetic detection. 3. Verify with GPS/total station coordinates.
Volume Calculation	Compute cut and fill quantities.	1. Create a digital terrain model (DTM) from surveyed points. 2. Compare existing vs. design elevations. 3. Apply prismoidal or grid-based methods to obtain volumes.

4. Problem Solving Workflow (Universal)

1. Define the Objective

Introduction to Land Survey Problem Solving

- What information is required? (e.g., coordinates, elevations, area)

2. Collect Existing Data

- Legal documents, prior surveys, satellite imagery, GIS layers.

3. Select Survey Method(s)